OMRON Industrial Automation

P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

Specifications

Applicable product family	G2R-1-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	61.0 mm
Product Height (unpacked)	79 mm
Product Width (unpacked)	15.5 mm
Terminal type	Screw
Color	Black
Hold down clip included	✔
Release Lever included	✔
Applicable ferrules	Forked terminals, Round terminals

Fits to

G2R-1-S 120VAC (S)
Relay, plug-in, SPDT, 10 A, mechanical indicator, 120 VAC

G2R-1-S 12VDC (S)
Relay, plug-in, SPDT, 10 A, mechanical indicator, 12 VDC

G2R-1-S 230VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 230 VAC

G2R-1-S 240VAC (S)
Relay, plug-in, SPDT, 10 A, mechanical indicator, 240 VAC

G2R-1-S 24VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 24 VAC

G2R-1-SD 24VDC (S)
Relay, plug-in, SPDT, 10 A, mech. indicator, diode, 24 VDC

G2R-1-SN 120VAC (S)
Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC

G2R-1-SN 12VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility, 12 VAC

G2R-1-SN-AP3 230VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating

G2R-1-SN-AP3 24VDC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, gold-plated contacts, LED indicator

G2R-1-SND 48VDC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility

G2R-1-SND-AP3 24VDC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating

G2R-1-SNDI 12VDC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC

G2R-1-SNDI-AP3 24VDC (S)
Relay, plug-in, 5-pin, SPDT, 10 A gold plate contacts, mech & LED indicators, coil suppressor, lockable test button, label facility

G2R-1-SNI 110VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility, 110 AC

G2R-1-SNI 120VAC (S)
Relay, plug-in, SPDT, 10 A, mech. & LED indicator, test button, 120 VAC

G2R-1-SNI 230VAC (S)
Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility

G2R-1-SNI 48VAC (S)
Relay, plug-in, SPDT, 10 A, mechanical & LED indicator, lockable testbutton, 48 VAC

Accessories

	P2DN-CP100	Box of 100 caps for P2DN short bar: insulation cap for the short bar cut, blue color
	PFP-100N	DIN-rail mounting track, 35 x 7.3 mm, 1 m length
	PFP-100N2	DIN-rail mounting track, 35x16mm, 1m length
	PFP-50N	Din rail track, 500 mm
	PFP-M	End plate
	PFP-S	Spacer
	XW5Z-EP12	Separator Plate for terminal blocks, 12 mm width
	XW5Z-EP6	End bracket for terminal blocks, 6 mm width

Downloads

CAD Library

EAC Mark removal

Discontinuation Notice

EN PDF 221 KB

G2R-_-S (S) General-purpose Relay

Datasheet

EN PDF 3.32 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 31 March, 2025. Click here for terms of use.