OMRON Industrial Automation

G2RV-ST500 24VDC

Slimline relay 6 mm incl. socket, SPDT, 6 A, Push-in terminals, 24 VDC

Specifications

Coil voltage	24 V
Contact description	SPDT
Contact material	Ag alloy
Features	Diode, LED, Transparent case, With mechanical indicator
Mounting method	DIN rail
Poles	1
Rated carry current	6 A
Terminal type	Push-in Plus
Usage	Interface
Operation voltage	DC

Accessories

G2RV-1-S-G 21VDC

Relay, SPCO, 6 A contacts, for replacement in G2RV-SR*00 24DC or 24 VAC/DC

Downloads

CAD Library

EAC Mark removal

Discontinuation Notice

EN PDF 221 KB

G2RV-ST & G3RV-ST

Datasheet

EN PDF 8.78 MB

G2RV-ST G3RV-ST Slim I/O Relay/Slim I/O Solid State Relay

Flyer

EN PDF 2.72 MB

Industrial Relays

Brochure

EN PDF 2.77 MB

OMRON Manufacturing Know-How: High Quality Relays

Leaflet

EN PDF 449 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 31 March, 2025. Click here for terms of use.